AUTHOR INDEX

Aizawa, M., 79
Auerbach, A., 195

Bergveld, P., 251
Boucher, J., 365
Boyer, A., 131

Chandler, G. K., 223
Charles, E., 131
Chiba, T., 79
Ciureanu, P., 229
Colin, Y., 263
Coursant, R. H., 351

Danielsson, B., 139
Demarne, V., 301
Doersam, D., 195
Dong-Bai Ye, 315

Eddowes, M. J., 223
Eyraud, L., 351
Eyraud, P., 351

Fink, M., 351
Fukumoto, H., 243

Ghers, M., 263
Graf, H.-J., 159
Grisel, A., 301
Groubert, E., 131
Guyader, J., 263

Haruta, M., 339
Hirata, M., 63
Homma, Y., 71
Huang, P. H., 329

Igarashi, I., 53
Ito, N., 165

Kamimura, K., 71
Kimura, J., 165
Kittilsland, G., 203
Kobayashi, A., 29
Kobayashi, T., 339
Kodato, S., 11
Koike, R., 11
Korony, G., 229
Kuriyama, T., 165
Kurobe, T., 323

Lalevic, B., 275
Lambrechts, M., 287
Laurent, Y., 263
Lescure, M., 365
Lübbers, D. W., 159
Lundström, I., 139

Mehregany, M., 375
Mitsui, S., 147
Morrison, S. Roy, 89
Mosbach, K., 139
Murakami, K., 315

Nakamoto, S., 165
Nakane, M., 339
Narayanaswamy, R., 293

Onuma, Y., 71
Opitz, N., 159
Ohta, Y., 323
Oyabu, T., 323

Paszczynski, S., 287
Pedersen, K., 203
Pietrucha, B., 275
Pribat, D., 173

Rossé, G., 263
Russell, D. A., 293

Sadaoka, Y., 147, 243
Sakai, Y., 147, 243
Sano, H., 339
Sansen, W., 287
Santiago-Aviles, J. J., 117
Sasaki, A., 43
Sears, W. M., 89
Senturia, S. D., 375
Shinohara, H., 79
Smela, E., 117
Stemme, G., 203
Stenberg, M., 203
Suls, J., 287
Suzuki, K., 63

Takahashi, K., 1, 3
Tanigawa, H., 63
Tellier, J. M., 351

van der Schoot, B., 251
van Putten, A. F. P., 103
Velasco, G., 173

Wenzel, S. W., 391
White, R. M., 391
Winquist, F., 139

Yamamoto, T., 315

© Elsevier Sequoia/Printed in The Netherlands

SUBJECT INDEX

Alarm detector
of gas leaks, 'intelligent', 323
Anisotropic etching
of Si in hydrazine, 375
Annealing
effects of, and geometry optimization on thin magnetoresistive head, 229
Anodic oxidation etch-stop
silicon diaphragm pressure sensors fabricated by, 63
Array transducers
characterization of modified Pb titanate piezoceramics; application to design of, 351

Bioanalytical applications
biosensors based on thermistors and semiconductors and their, 139
Biofilms
silicon sensor for measurement of liquid flow and thickness of fouling, 203
Biosensors
based on thermistors and semiconductors and their bioanalytical applications, 139

Carbon monoxide
gas sensor, integrated low-power thin-film, on Si, 301
selective CO sensor using Ti-doped α-Fe_2O_3 with coprecipitated ultrafine particles of Au, 339
Chemical sensing
coulometric sensors, application of sensor–actuator system for long-term stability in, 251
Chemical species
optical sensors for dissolved ionic, 293
Coulometric sensors
application of sensor–actuator system for long-term stability in chemical sensing, 251
Current
constant voltage, constant, Wheatstone bridge configuration, 103

Dynamic sensors
semiconductor, 53

Energy control
microionic gas sensor for pollution and, in consumer market, 173
Enzyme-immobilized membranes
in multibiosensors, lift-off method for patterning, 165
Enzyme-mediated
pH-sensitive FET devices, problems of non-linear response, 223
Enzyme microsensor
for glucose with electrochemically synthesized enzyme–polyaniline film, 79

FET devices
enzyme-mediated, pH-sensitive; problems of non-linear response, 223
Fiber loop
catheter-mounted pressure transducer using, 195
Fiber sensor
versatile twisted optical, 117
Fluorescence quenching
of indicator-treated silicone rubber membranes, oxygen sensor for temperature range 300 to 500 K based on, 159

Gas leaks
'intelligent' alarm detector of, 323
Gas sensor(s)
CO, integrated low-power thin-film, on Si, 301
microionic, for pollution and energy control in consumer market, 173
Pt hot wire, design of, 89
Geometry optimization
effects of annealing and, on thin magnetoresistive head, 229
Germanium
oxygen ionosorption on compressed semiconducting powders of Zn and Ge oxynitrides, 263

© Elsevier Sequoia/Printed in The Netherlands

Glucose
enzyme microsensor for, with electrochemically synthesized enzyme–polyaniline film, 79
Gold
selective CO sensor using Ti-doped α-Fe_2O_3 with coprecipitated ultrafine particles of, 339

Halogenated polymeric humidity sensors, 329
High-voltage line
remote control for overhead, 365
Humidity sensitive
and water-resistive polymeric materials, 243
Humidity sensor(s)
halogenated polymeric, 329
using Zr phosphates and silicates; improvements of humidity sensitivity, 147
Hydrazine
anisotropic etching of Si in, 375
Hydrocarbon gases
detection of, using Pd-MNOS capacitors, 275
Hydrogen leak detector
integrated, with tunnel MIS structure, 315

Ionic chemical species
optical sensors for dissolved, 293
Iron
selective CO sensor using Ti-doped α-Fe_2O_3 with coprecipitated ultrafine particles of Au, 339

Laser powers
thin-film thermopiles for measuring high, 131
Lead
characterization of modified Pb titanate piezoceramics; application to design of array transducers, 351
Liquid flow
silicon sensor for measurement of, and thickness of fouling biofilms, 203

Magnetoresistive head
effects of annealing and geometry optimization on thin, 229
Measurement
and sensors, 29

Microionic gas sensor
for pollution and energy control in consumer market, 173
Microsensor
enzyme, for glucose with electrochemically synthesized enzyme–polyaniline film, 79
MIS structure
integrated H leak detector with tunnel, 315
MNOS capacitors
Pd-, detection of hydrocarbon gases using, 275
Multibiosensors
lift-off method for patterning enzyme-immobilized membranes in, 165

Optical fiber sensor
versatile twisted, 117
Optical sensing devices
and functional, 43
Optical sensors
for dissolved ionic chemical species, 293
Oxygen inosorption
on compressed semiconducting powders of Zn and Ge oxynitrides, 263
Oxygen sensor
for temperature range 300 to 500 K based on fluorescence quenching of indicator-treated silicone rubber membranes, 159

Pd-MNOS capacitors
detection of hydrocarbon gases using, 275
pH-sensitive
enzyme-mediated, FET devices; problems of non-linear response, 223
Piezoceramics
characterization of modified Pb titanate; application to design of array transducers, 351
Piezoresistive elements
of polycrystalline semiconductor thin films, 71
Platinum
hot wire gas sensors, design of, 89
Pollution
microionic gas sensor for, and energy control in consumer market, 173
Polyaniline
enzyme–, film, electrochemically

synthesized, enzyme microsensor for glucose with, 79
Polymeric materials
humidity-sensitive and water-resistive, 243
Pressure sensors
silicon diaphragm, fabricated by anodic oxidation etch-stop, 63
Pressure transducer
catheter-mounted, using fiber loop, 195

Remote control
for overhead high-voltage line, 365
Ruthenium dioxide
thick-film voltammetric sensors based on, 287

Semiconducting powders
of Zn and Ge oxynitrides, oxygen ionosorption on compressed, 263
Semiconductor(s)
biosensors based on thermistors and, and their bioanalytical application 139
dynamic sensors, 53
thin films, piezoresistive elements of polycrystalline, 71
wafer alignment, inexpensive and accurate two-sided, 391
Sensing devices
optical and functional, 43
Sensor–actuator system
for long-term stability in chemical sensing; coulometric sensor, application of, 251
Sensor materials
for the future; intelligent materials, 3
Silicon
anisotropic etching of, in hydrazine, 375
integrated low-power thin-film CO gas sensor on, 301
Silicon diaphragm
pressure sensors fabricated by anodic oxidation etch-stop, 63
Silicon films
use of amorphous, as sensors, 11
Silicon sensor
for measurement of liquid flow and thickness of fouling biofilms, 203
Silicone rubber membranes
oxygen sensor for temperature range 300 to 500 K based on fluorescence quenching of indicator-treated, 159

Thermistors
biosensors based on, and semiconductors and their bioanalytical applications, 139
Thermopiles
thin-film, for measuring high laser powers, 131
Titanium
selective CO sensor using Ti-doped α-Fe_2O_3 with coprecipitated ultrafine particles of Au, 339
Transducer
catheter-mounted pressure, using fiber loop, 195

Voltage
constant, constant current Wheatstone bridge configuration, 103
Voltammetric sensors
thick-film, based on Ru dioxide, 287

Wafer alignment
semiconductor, inexpensive and accurate two-sided, 391
Water resistive
humidity sensitive and, polymeric materials, 243
Wheatstone bridge configuration
constant voltage constant current, 103

Zinc
oxygen ionosorption on compressed semiconducting powders of Zn and Ge oxynitrides, 263
Zirconium
humidity sensor using Zr phosphates and silicates; improvements of humidity sensitivity, 147